



PRODUKTBESCHREIBUNG

- » Schaft Ø6 mm
- » Passt sich durch flexible Schleiflamellen an Kontur an
- » Zum Vorschleifen
- » Schleifleinen aus Normalkorund
- » Bis 55 HRC



d3	l	d1	l1	Korn	 Stk. / VPE	Nr.	EUR
6	50	40	10	80	10	V 74964/40/10/ 80	<>
6	50	40	10	120	10	V 74964/40/10/120	<>
6	50	40	10	150	10	V 74964/40/10/150	<>
6	50	40	10	240	10	V 74964/40/10/240	<>
6	50	40	10	320	10	V 74964/40/10/320	<>
6	60	40	20	80	10	V 74964/40/20/ 80	<>
6	60	40	20	120	10	V 74964/40/20/120	<>
6	60	40	20	150	10	V 74964/40/20/150	<>
6	60	40	20	240	10	V 74964/40/20/240	<>
6	60	40	20	320	10	V 74964/40/20/320	<>
6	60	50	20	80	10	V 74964/50/20/ 80	<>
6	60	50	20	120	10	V 74964/50/20/120	<>
6	60	50	20	150	10	V 74964/50/20/150	<>
6	60	50	20	240	10	V 74964/50/20/240	<>
6	60	50	20	320	10	V 74964/50/20/320	<>