

ISO  
15488-A

DIN  
6499




### PRODUCT DESCRIPTION

- » Increased service life due to FAHRION Protect corrosion protection coating
- » With sealing plugs for inner coolant supply up to 100 bar
- » With inner square for positive engagement of the tap

### APPLICATION

- » For thread cutting



SW	d	l	Type	ER	d1	No.	EUR
2.1	16.7	27.5	4031E	16	2.8	HWZ 9090/16/ 2,8	<>
2.7	16.7	27.5	4031E	16	3.5	HWZ 9090/16/ 3,5	<>
3.55	16.7	27.5	4031E	16	4.5	HWZ 9090/16/ 4,5	<>
5	16.7	27.5	4031E	16	6	HWZ 9090/16/ 6	<>
5.6	16.7	27.5	4031E	16	7	HWZ 9090/16/ 7	<>
6.3	16.7	27.5	4031E	16	8	HWZ 9090/16/ 8	<>
7.1	16.7	27.5	4031E	16	9	HWZ 9090/16/ 9	<>
3.55	25.7	34	4282E	25	4.5	HWZ 9090/25/ 4,5	<>
5	25.7	34	4282E	25	6	HWZ 9090/25/ 6	<>
5.6	25.7	34	4282E	25	7	HWZ 9090/25/ 7	<>
6.3	25.7	34	4282E	25	8	HWZ 9090/25/ 8	<>
7.1	25.7	34	4282E	25	9	HWZ 9090/25/ 9	<>
8	25.7	34	4282E	25	10	HWZ 9090/25/10	<>
9	25.7	34	4282E	25	11	HWZ 9090/25/11	<>
9	25.7	34	4282E	25	12	HWZ 9090/25/12	<>
11.2	25.7	34	4282E	25	14	HWZ 9090/25/14	<>
12.5	25.7	34	4282E	25	16	HWZ 9090/25/16	<>