




PRODUCT DESCRIPTION

- » Shank Ø3 mm
- » Low material removal rate
- » Rubber bond, medium
- » High surface quality



Shape	Grit	d3	d1	l1	 Pcs. / PU	No.	EUR
A1  Cylinder	● 80	3	4	8	10	V 72522/ A1/ 4x 8/ 80	<>
	● 120	3	4	8	10	V 72522/ A1/ 4x 8/120	<>
	● 220	3	4	8	10	V 72522/ A1/ 4x 8/220	<>
	● 280	3	4	8	10	V 72522/ A1/ 4x 8/280	<>
	● 80	3	5	10	10	V 72522/ A1/ 5x10/ 80	<>
	● 120	3	5	10	10	V 72522/ A1/ 5x10/120	<>
	● 220	3	5	10	10	V 72522/ A1/ 5x10/220	<>
	● 280	3	5	10	10	V 72522/ A1/ 5x10/280	<>
	● 80	3	6	10	10	V 72522/ A1/ 6x10/ 80	<>
	● 120	3	6	10	10	V 72522/ A1/ 6x10/120	<>
	● 220	3	6	10	10	V 72522/ A1/ 6x10/220	<>
	● 280	3	6	10	10	V 72522/ A1/ 6x10/280	<>
	● 80	3	8	10	10	V 72522/ A1/ 8x10/ 80	<>
	● 120	3	8	10	10	V 72522/ A1/ 8x10/120	<>
	● 220	3	8	10	10	V 72522/ A1/ 8x10/220	<>
	● 280	3	8	10	10	V 72522/ A1/ 8x10/280	<>
	● 80	3	10	10	10	V 72522/ A1/10x10/ 80	<>
	● 120	3	10	10	10	V 72522/ A1/10x10/120	<>
	● 220	3	10	10	10	V 72522/ A1/10x10/220	<>
	● 280	3	10	10	10	V 72522/ A1/10x10/280	<>
J1  Ball	● 120	3	8	-	10	V 72522/ J1/ 8/120	<>
	● 120	3	10	-	10	V 72522/ J1/10/120	<>

REFERENCE VALUES

